



SkyView

Portable Ground Control Station

The ruggedized Ground Control Station for harsh environments

Features:

- Field proven SkyView GCS Software included
 - NATO STANAG 4586 Compliant
 - 15" Sun-readable display, 1600 nits
 - Up to 8 Hours of battery operation
 - Joystick with 2 buttons for vehicle or camera control
 - Throttle for vehicle speed control or camera zoom
 - Integrated computer
 - Intel® Dual Core Processor
 - 3D graphics card
 - 8 GB RAM
 - 256 GB Solid State Disk with optional encryption
 - 4 hardware switches (software reconfigurable)
 - High quality keyboard and mouse
 - External or Internal MPEG4 network video server
 - External or Internal Data Modem with the following optional frequencies:
[145 - 185 MHz, 410 - 480 MHz, 869.4 MHz - 869.65 MHz (default), 902 - 928 MHz, 2.390 - 2.4835 GHz or 3.3 - 3.5 GHz]
 - External connectors:
 - Optional analog video input BNC connector
 - 10/100Mbit Ethernet
 - USB 2.0
 - +12VDC (MIL-C-26482) for recharging
 - IP67 Environmental protection class when closed
 - IP62 Environmental protection class when lid opened
 - Wide operating temperature range: -15 to 50°C
 - Dimensions: 550 x 430 x 215 mm L x W x H
 - Weight: 14.2 Kg
- Optional items:**
- Touch screen
 - Integrated GPS-receiver
 - Extra battery pack (up to 12 Hours of operation)
 - Customer supplied data modem integration

